

PART NUMBER

PFF57-702

DESCRIPTION

FRONT LOWER ARM REAR BUSH

INSTALLATION GUIDE

Contents (parts per pack):

2 x Polyurethane A Bushes 1 x PTFE/Silicone Grease

2 x Polyurethane B Bushes 2 x Stainless Steel Sleeves

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to;
- -wheel alignment to be checked and adjusted as required after any suspension work.
- -All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- 1. Remove the front lower arm from the vehicle and remove the original rubber bush.
- 2. Clean any dirt and corrosion from the surface of the shaft, as shown in Figure 1.
- 3. Insert polyurethane part A into the stainless steel sleeve first and then fit part A and sleeve on the arm shaft, as shown in Figure 2.

Note: Do not fit part A onto the shaft without the stainless steel sleeve over it.

- 4. Apply some of the supplied grease into the bore of the polyurethane part B and fit the polyurethane bush on the stainless steel sleeve, as shown in Figure 3.
- 5. Refit the front lower arm to the vehicle and tension all hardware to manufacturers recommended torque settings.





Clean shaft Surface. *Figure 1*



Figure 3







Figure 2