

PART NUMBER

PFF76-604

DESCRIPTION

TOYOTA SUPRA FRONT UPPER WISHBONE BUSH

INSTALLATION GUIDE

Contents (parts per pack):

8 x Polyurethane Bushes

1 x PTFE/Silicone Grease

- 4 x Stainless Steel Sleeves
- 4 x Zinc Plated Mild Steel Washers

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to:
- -wheel alignment to be checked and adjusted as required after any suspension work.
- -All fasteners must be tightened to manufacturer's torque settings.

CONSTRUCTION OF THE PROPERTY O

Fitting Instructions:

- 1. Remove the upper wishbone from the car.
- 2. Press out the original bushes including any outer shells from the wishbone.
- 3. Clean away any corrosion or dirt from the vacant bore.
- 4. Press the bushes into either side of the arm.
- 5. Apply the supplied grease to the bore and outside faces of the bushes and push in the stainless steel sleeve.
- 6. Offer the wishbone back up to the car, and place the supplied washers in between the bush and the subframe.
- 7. The original washers should be retained and refitted to the outside of each bush.
- 8. Refit the nut and bolt, and tension all hardware to the manufacturers recommended torque settings.

