

PART NUMBER

DESCRIPTION

PFF85-803*

FRONT ANTI-ROLL BAR BUSH

INSTALLATION GUIDE

*Note:

Please check anti-roll bar diameter size for correct bush sizing.

Sizes available: 21.7mm, 23.2mm, 24mm & 25mm.

Product description:

This part replaces OEM part numbers 5Q0411303L, 5Q411303M, 5Q411303N, 5Q411303AB.

Contents (parts per pack):

2 x Polyurethane Bushes

1 x Grease

Please read the complete fitting instructions and check package components before fitment.

These fitting instructions are to be used as a guide and in conjunction with workshop manual.

It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to;
- -wheel alignment to be checked and adjusted as required after any suspension work.

All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- 1. Remove the front anti roll bar from the car.
- 2. Secure the bar firmly on a vice and slowly drill away the swaged section from the bottom of the brackets to separate the brackets from the bush and the anti-roll bar.
 - Note: DO NOT drill into the brackets more than required. Fig A.
- 3. Remove the rubber bushes. Clean any dirt and corrosion from the brackets and the anti-roll bar.
- 4. Fit the new PU bushes on the bar. Re-fit the brackets on the bushes Fig B.
- 5. Fit back anti roll bar to the car. Tension all hardware to manufacturers recommended torque settings.



POWERFLEX +44 (0) 1895 460033