

**PART NUMBER** 

# PFR1-1011

**DESCRIPTION** 

#### **REAR LOWER ARM OUTER BUSH**

#### **INSTALLATION GUIDE**

### Contents (parts per pack):

4 x Polyurethane Bushes 1 x PTFE/Silicone Grease

2 x Zinc Plated Steel Outer Shells 2 x Stainless Steel Sleeves

4 x Zinc Plated Steel Washers

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to;
- -wheel alignment to be checked and adjusted as required after any suspension work.
- -All fasteners must be tensioned to manufacturer's torque settings.

## **Fitting Instructions:**

- 1. Remove the original inner bush from the arm.
- 2. Clean any dirt and corrosion from the bore of the arm and file off any sharp edges.
- 3. Push the outer shell into the arm with the larger diameter fitting towards the outside of the car until the lip sits against the arm, as shown in Figure 1.
- 4. Push the polyurethane bushes into the metal outer shell.
- 5. Apply the supplied grease into the bore of the polyurethane bushes and insert the stainless steel sleeve into the bore of the bush.
- 6. Re-fit the arm back to the car and tension all hardware to manufacturers recommended torque settings.



