

PART NUMBER

PFF26-116

DESCRIPTION

Rear Anti Roll Bar Drop Link Bush

INSTALLATION GUIDE

Contents (parts per pack):

- 2 x Polyurethane Bushes
- 2 x Stainless Steel Sleeves
- 1 x PTFE/Silicone Grease

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to;
- -wheel alignment to be checked and adjusted as required after any suspension work.
- -All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- 1. Remove the original rubber bush from the arm, and clean any dirt and corrosion from the bore in the arm.
- 2. Press the cotton reel style bush into the bore of the drop link, as shown in figure 1.

Tip: Apply some washing up to the bush and the bore of the drop link to ease fitment of the bush.

- 3. Apply some of the supplied grease to the bore of the bush.
- 4. Insert the stainless steel sleeve into the bore of the bush until sitting flush on both sides.
- 5. Refit the drop link bush to the lower rear arm and the anti-roll bar. Tension all hardware to manufacturers recommended torque settings



Figure 2



Figure 3



